

It's time for a filter cleaning!



Pool PSI Gauge

For earth filters: clean the pool filter using strip kwik as follows:

1. Remove elements from filter Rinse off debris
2. Fill a clean plastic trash can with enough water to cover the element and 1 qt Strip Kwik
3. Let filter element soak for 12 - 24 hours
4. Rinse thoroughly with water
5. Replace elements in filter and resume normal operation

For Cartridge Filters: Clean the pool filter using Kleen It as follows:

1. Turn pump off and rinse off loose dirt from filter elements.
2. Apply product by spraying directly onto filter elements. If needed, lightly brush heavy grease spots.
3. Allow elements to sit for 1 hour.
4. Rinse elements thoroughly with water.
5. Reassemble filter and resume normal operation



Strip-Kwik

For Sand Filters: Clean the pool filter using STRIP KWIK as follows:

1. Thoroughly backwash filter (backwash - rinse - backwash - rinse)
2. Turn pump off
3. Pour 1 qt Strip Kwik into pump pot (cleaner is red in color)
4. Turn pump on long enough for chemical to disappear from pump pot (approximately 2-3 seconds)
5. Turn pump off
6. Let cleaner sit in filter tank for 12 - 24 hours
7. Backwash until discharge turns from red to clear
8. Return to normal operation.



Kleen it

